

-2-

MIKOS-101                      AMENDMENT WITH RCE                      07650001aa  
Amendment dated 07/27/2006                      Reply to office action mailed 01/27/2006

The following is a complete listing of all claims in the application, with an indication of the status of each:

**Listing of claims:**

- 1            1. (currently amended) System for authenticating digital information,
- 2            comprising:
- 3                      a) an image acquisition device for producing an original array of
- 4            two-dimensional digital information;
- 5                      b) means for obtaining current date and time information from satellite
- 6            or radio broadcasts;
- 7                      c) means for obtaining current location information from satellite or
- 8            radio broadcasts;
- 9                      d) means for identifying a Sensor ID for the image acquisition device;
- 10                      e) an encoder for converting date/time, location, and Sensor ID into
- 11            two-dimensional format called the Encoded Data Array;
- 12                      f) an embedder for combining the Encoded Data Array and the
- 13            Original Array into a new Composite Array
- 14                      h) a Transmission device to transfer the Composite Array to a
- 15            recipient;
- 16                      n) means for comparing said transferred Composite Array to said
- 17            Encoded Data Array, said comparing means thereby being able to use said
- 18            Encoded Data Array to determine whether the information in said Encoded
- 19            Data Array is embedded in said Composite Array, said comparing means also
- 20            being able to separately determine whether said date/time information, said
- 21            location information, and said Sensor ID information is embedded in said
- 22            Composite Array, said comparing means being further limited by being able to

-3-

MIKOS-101

AMENDMENT WITH RCE

07650001aa

Amendment dated 07/27/2006

Reply to office action mailed 01/27/2006

- 23 make said determination without extracting or otherwise decoding the  
24 information in said Encoded Data Array;  
25 j) a decoder with fault indicator when date/time, location, and source  
26 cannot be decoded;  
27 k) an Encoding Extractor for removing the Encoded Data Array from  
28 the Composite Array;  
29 l) means for restoring the Original Array at pixel locations used for the  
30 Encoding; and  
31 m) means for determining changes between the Restored Original  
32 Array and the Original Array.
- 1 2. (previously presented) System as in Claim 1 in which the Original Array  
2 size is increased by a factor and subpixels are used in steps f, h, n, j, k, l, and  
3 m.
- 1 3. (previously presented) System as in claim 20 in which the encryption of  
2 step g and decryption of step i is repeated more than one time.
- 1 4. (previously presented) System as in Claims 1 or 2 in which the encryption  
2 process involves scrambling the pixels or subpixels.
- 1 5. (previously presented) System as in Claims 1 or 2 in which steps b and c  
2 utilize the GPS (Global Positioning Satellite) system.
- 1 6. (previously presented) System as in Claims 1 or 2 in which the Decoder  
2 utilizes flash correlation to select pixel locations of the Encoded Data Array  
3 and test for authenticity.

-4-

MIKOS-101

AMENDMENT WITH RCE

07650001aa

Amendment dated 07/27/2006

Reply to office action mailed 01/27/2006

- 1        7. (previously presented) System as in Claims 1 or 2 in which the Sensor ID  
2        in step d includes a biometric identifier of the User of the image acquisition  
3        device.
- 1        8. (previously presented) System as in Claims 1 or 2 in which the Sensor ID  
2        in step d includes the serial number and odometer setting of the image  
3        acquisition device of step a.
- 1        9. (previously presented) System as in Claims 1 or 2 in which the change  
2        detector of step m evaluates subsections of the Restored Original Array and  
3        the Original Array to localize areas of difference.
- 1        10. (previously presented) System as in Claim 6 in which flash correlation is  
2        used to verify that the encoded data is the same as data which is expected to be  
3        encoded into a particular Original Array.
- 1        11. (previously presented) System as in Claim 6 in which flash correlation is  
2        used to identify the encoded data by exhaustive comparison against each  
3        possible value for each of date/time, location, and source.
- 1        12. (previously presented) System as in Claims 1 or 2 in which date/time,  
2        location, and source are annotated onto the Encrypted Composite Array.
- 1        13. (previously presented) System as in Claims 1 or 2 in which the encoded  
2        data provides the key to the encryption and decryption algorithms.

-5-

MIKOS-101

AMENDMENT WITH RCE

07650001aa

Amendment dated 07/27/2006

Reply to office action mailed 01/27/2006

- 1        14. (previously presented) System of Claims 1 or 2 in which the operation of  
2        the image acquisition device is triggered by the change of status of another  
3        device.
- 1        15. (original) System of Claim 14 in which the triggering device is a face  
2        recognition system.
- 1        16. (original) System of Claim 14 in which the triggering device is a speed  
2        sensor.
- 1        17. (original) System of Claim 14 in which the triggering device is an alarm  
2        condition sensor.
- 1        18. (previously presented) System of Claims 1 or 2 in which the Encoding is  
2        performed by overlaying a pattern of pixels of a particular color or grey scale  
3        value.
- 1        19. (previously presented) System of Claims 1 or 2 in which the Encoding is  
2        performed by steganography.
- 1        20. (previously presented) System of Claims 1 or 2, further comprising:  
2                g) an encrypter for encrypting the Composite Array;  
3                i) a decrypter to restore the Composite Array.
- 1        21. (currently amended) A method for authenticating digital images,  
2        comprising the steps of:  
3                capturing a digital image;

-6-

MIKOS-101

**AMENDMENT WITH RCE**

07650001aa

Amendment dated 07/27/2006

Reply to office action mailed 01/27/2006

4            recording authentication information at the time and place of said  
5            capturing, said authentication information being unique to said digital image  
6            and comprising a plurality of pieces of information, including at least one  
7            piece of information from a source independent of said capturing;  
8            encoding said authentication information into a data array mapable to  
9            said digital image;  
10           mapping said data array to said digital image, thereby creating a  
11           composite array;  
12           optionally encrypting said composite array;  
13           optionally annotating said composite array;  
14           comparing said data array, optionally encrypted and annotated, to a  
15           target composite array, wherein said comparing determines whether said  
16           authentication information is embedded in said target composite array, said  
17           comparing also being able to separately determine whether each of said  
18           plurality of pieces of information is embedded in said target composite array,  
19           said comparing being further limited by being able to make said determination  
20           without extracting or otherwise decoding information in said data array,  
21           thereby proving that said target composite array is an authentic copy of said  
22           composite array.

1           22. (original) The method of claim 21, wherein said at least one piece of  
2           information from a source independent of said capturing is GMT time  
3           information.

1           23. (original) The method of claim 21, wherein said at least one piece of  
2           information from a source independent of said capturing is GPS location  
3           information.

-7-

MIKOS-101

AMENDMENT WITH RCE

07650001aa

Amendment dated 07/27/2006

Reply to office action mailed 01/27/2006

- 1        24. (original) The method of claim 21, wherein said at least one piece of  
2        information from a source independent of said capturing is GMT time  
3        information and GPS location information.
- 1        25. (previously presented) The method of claim 21, wherein said comparing  
2        step is flash correlation of said data array with said target composite array.
- 1        26. (previously presented) The method of claim 25, wherein said digital  
2        image is a sequence of digital images, there being a unique set of  
3        authenticating information for each digital image in said sequence and a  
4        corresponding unique data array, there being a unique composite array  
5        corresponding to each digital image in said sequence, wherein said composite  
6        array is a sequence of composite arrays and said target composite array is a  
7        sequence of target composite arrays, and wherein said flash correlation  
8        determines whether said sequence of target composite arrays is an authentic  
9        copy of said sequence of composite arrays.
- 1        27. (previously presented) The method of claim 26, wherein said sequence of  
2        digital images is a video image and said flash correlation is done in real time.
- 1        28. (currently amended) A system for authenticating digital images,  
2        comprising:  
3                means for capturing a digital image;  
4                means for recording authentication information at the time and place of  
5        said capturing, said authentication information being unique to said digital  
6        image and comprising a plurality of pieces of information, including at least  
7        one piece of information from a source independent of said capturing;

-8-

MIKOS-101

AMENDMENT WITH RCE

07650001aa

Amendment dated 07/27/2006

Reply to office action mailed 01/27/2006

8 means for encoding said authentication information into a data array  
9 mapable to said digital image;  
10 means for mapping said data array to said digital image, thereby  
11 creating a composite array;  
12 means for optionally encrypting said composite array;  
13 means for optionally annotating said composite array;  
14 means for comparing said data array, optionally encrypted and  
15 annotated, to a target composite array, wherein said comparing determines  
16 whether said authentication information is embedded in said target composite  
17 array, said comparing means also being able to separately determine whether  
18 each of said plurality of pieces of information is embedded in said target  
19 composite array, said comparing means being further limited by being able to  
20 make said determination without extracting or otherwise decoding information  
21 in said data array, thereby proving that said target composite array is an  
22 authentic copy of said composite array.

1 29. (original) The system of claim 28, wherein said at least one piece of  
2 information from a source independent of said capturing is GMT time  
3 information.

1 30. (original) The system of claim 28, wherein said at least one piece of  
2 information from a source independent of said capturing is GPS location  
3 information.

1 31. (original) The system of claim 28, wherein said at least one piece of  
2 information from a source independent of said capturing is GMT time  
3 information and GPS location information.

-9-

MIKOS-101

AMENDMENT WITH RCE

07650001aa

Amendment dated 07/27/2006

Reply to office action mailed 01/27/2006

1 32. (previously presented) The system of claim 28, wherein said comparing  
2 step is flash correlation of said data array with said target composite array.

1 33. (previously presented) The system of claim 32, wherein said digital  
2 image is a sequence of digital images, there being a unique set of  
3 authenticating information for each digital image in said sequence and a  
4 corresponding unique data array, there being a unique composite array  
5 corresponding to each digital image in said sequence, wherein said composite  
6 array is a sequence of composite arrays and said target composite array is a  
7 sequence of target composite arrays, and wherein said flash correlation  
8 determines whether said sequence of target composite arrays is an authentic  
9 copy of said sequence of composite arrays.

1 34. (previously presented) The system of claim 33, wherein said sequence of  
2 digital images is a video image and said flash correlation is done in real time.